

CI

2 Slot DVB-CI Module



OVERVIEW

The 'CI' module supports two types of descrambling: CAM-based (DVB-Common Interface) and BISS descrambling.

It can be installed to support most Conditional Access or BISS-1/E descrambling.

KEY FEATURES

- 2 slots for DVB-CI descrambling
- Capable of BISS-1/E descrambling
- Platform-based Modular Design

ORDERING INFORMATION

Model	Description
WAV-DMPSP-CI	2 Slot DMP-SMP DVB-CI Module
WAV-DMPSP-BISS	DMP-SMP BISS Module
WAV-SMP100-CHASSIS	Chassis (1RU, embedded MUX and IP/ASI, 3 x slots)
WAV-DMP900-CHASSIS	Chassis (1RU, embedded MUX, 6 x slots, Dual PSU, hot-swappable)

SPECIFICATIONS

DVB-CI DESCRAMBLING

Interface: 2 x PCMCIA CI Slots
Methods: Simul/Multi-descrambling (Depending on CAMs)
Supported CAMs: Support for all major CAMs

BISS DESCRAMBLING

Maximum Number of Services: 16 (Depending on multi-service CAM)
BISS Modes: BISS-1, BISS-E
BISS Descrambling: Service-level BISS descrambling
Maximum Data Rate: Up to 640 Mbps
Maximum number of TS: 16 Transport Streams
Maximum BISS keys: 1024 (license controlled)

PLATFORM

Power Consumption: Maximum 5W